

## MAIN FEATURES

Access mode	Frontal / Lateral
Clamping system	Automatic
Mixing phases	4
Mixing speed	0-1300 rpm
Display	Alphanumeric 20 x 4
N° of personalizing mixing programs	30
Impeller drops saving device	Automatic
Impeller	Not included
Clamping adapter (for containers smaller than 170 mm in diameter)	Optional

## POWER SUPPLY

Voltage	220 - 240 V L+N
Mains frequency	50/60 Hz
Maximum power absorbed	3,5 kW
Mixing self-braking motor power	3 kW
Impeller movement self-braking motor power	0,37 kW
Clamping system self-braking motor power	0,37 kW

## LOAD CAPACITY

Maximum can weight	40 kg
Can diameter (without adaptor): min - max	170 - 320 mm
Maximum can height	430 mm
Loading height	430 (+30) mm
Type of containers	Round / Oval

## LATERAL CONFIGURATION

Optoelectronic safe device	✓
Roller conveyors	Not included
Roller conveyors lenght	500 / 700 mm
Roller conveyors width	370 mm
Roller conveyors height	430 (+100) mm

## OVERALL DIMENSIONS

Machine dimensions (W x D x H)	870 x 840 x 1890 mm
Machine weight	320 kg
Shipping dimensions (W x D x H)	980 x 840 x 2060 mm
Shipping weight	340 kg

CERTIFICATION	CE
---------------	----



\*\* Data refers to base configuration machine; mixing speed and timing may vary according to can and/or product specifications

